



MORE FLEXIBILITY WITH SMARTER FEATURES

3 inch POS Printer
SRP-350III



HIGHLIGHTS



Powerful Printing Performance

- Fast printing up to 250mm/sec (25% faster than the SRP-350II)
- 4-type dithering options for graphic printing
- A family of the world-class SRP-350 line



Multiple interface choice

- Built-in USB with a choice of Serial, Parallel, or Ethernet



User-friendly Design

- Anti-jam guide
- Stand-alone or Space-saving wall-mount use
- 2" or 3" paper choice



BIXOLON[®]
 a Better Solution for your Business[™]

3 inch POS Printer SRP-350III



SPECIFICATIONS

Print Characteristics

Print Method

Direct Thermal

Print Speed

SRP-350III: 250 mm/sec

SRP-352III: 250 mm/sec

Print Resolution

SRP-350III: 180 dpi

SRP-352III: 203 dpi

Print Width

Up to 72 mm

Sensor

Paper End, Paper Near End, Cover Open

Media Characteristics

Media Type

Receipt

Media Width

80 mm / 58 mm

Media Roll Diameter

Up to 83 mm

Media Thickness

0.062 ~ 0.075 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)

145 x 204 x 146 mm

(5.70 x 8.03 x 5.74 inch)

Weight

1.55kg (3.41 lbs)

Power

EnergyStar Certified,

External Power Adaptor 100-240V AV, 50/60Hz

Drawer Port

2 ports (via y-type adaptor)

Performance Characteristics

Memory

64 Mbit SDRAM, 32 Mbit FlashROM

NV Image Memory

256 Kbytes (mono)

Receive Buffer

4 Kbytes

User Define Buffer

12 Kbytes

Interface

Dual Interface

USB V2.0 FS + Serial

USB V2.0 FS + Parallel

USB V2.0 FS + Ethernet

Environment Characteristics

Temperature

Operating: 0 ~ 45°C (32 ~ 113°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

Reliability

Printer Unit (MCBF)

70 Million Lines

Thermal Print Head (TPH)

150 km

Auto Cutter

1.8 Million Cuts

Software

Emulation

BXL / POS

Driver / Utility

Windows Driver, OPOS Driver, JPOS Driver,
Linux CUPS Driver, Mac Driver, Virtual COM USB/
Ethernet Driver, Utility Program

SDK

iOS SDK, Android SDK

Fonts / Graphics / Symbologies

Character Size

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24

KOR, CHN, JPN: 24 x 24

Characters Per Line

SRP-350III: Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

SRP-352III: Font A: 48 Font B, C: 64

KOR, CHN, JPN: 24

Character Sets

Alphanumeric: 95

Extended Graphics: 128 x 37 page

International: 32

Graphics

Supporting user-defined fonts, graphics, formats,
and logos

Barcode Symbologies

1D: Codabar, Code 39, Code 93, Code 128,
EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: Data Matrix, PDF417, QR code

BR-SRP-350III-EN-APR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

BIXOLON®

www.bixolon.com



POSIBERICA SOLUTIONS S.L.
Travessera de dalt 69 - 08024 Barcelona
Tel: 902 197 201 - Fax: 93 285 30 89
Mail: comercial@posiberica.com
Web: www.posiberica.com