



Retail



Hospitality



Banking



Ticketing



BIXOLON SRP-275II is more powerful and enhanced performance impact dot POS printer to address customers' needs in restaurant, hospitality and retail industries. The fastest speed in its class(5.1 lps) allows kitchen orders to print faster than ever with two color, black and red printing to highlight special offers and print logos. Compact size with embedded power supply maximizes the efficiency of working environment. Eco-friendly design of the lowest standby power and various international standards provide reliability of the SRP-275II to the users.

SPECIFICATIONS

PRINT

- PRINTING METHOD : 9 Pin Serial Dot Matrix
- PRINTING SPEED : Max 5.1 lps
- PRINTING WIDTH : 3.5mm(2.5 inch)
- RESOLUTION : Horizontal Resolution : 80 dpi
Vertical Resolution : 144 dpi
- CHARACTER SIZE (W X H dots) : Font A : 9 x 9 / Font B : 7 x 9
Korean : 17 x 9 / Chinese : 16 x 16
- CHARACTERS PER LINE : Font A: 35 (3half dot: 33) , Font B: 40,
Korean: 20, Chinese: 22 (3half dot: 21)
- CHARACTER SET : Alphanumeric Character : 95
Extended Character : STD - 128 x 27, CHN - 128 x 21,
KOR - 128 x 1
International Character : 48
- PRINTING DIRECTION : Bi-direction
- RECEIVE BUFFER : 64Kbyte
- NV IMAGE : 256Kbyte
- CUTTER TYPE : A: Tear-bar / C: Auto Cutter (Rotary)

PAPER

- WIDTH : 76.0 ± 0.5mm
- PAPER ROLL DIAMETER : 83mm
- PAPER ROADING : Easy Paper Loading

INK RIBBON

- COLOR : Black & Red
- RELIABILITY (CHARACTERS) : Black : 1,500,000 / Red : 750,000

RELIABILITY

- PRINTER UNIT (MCBF) : 18,000,000 lines
- HEAD : 300,000,000 dots/wire
- AUTO CUTTER : 1,500,000 cuts

INTERFACE : Serial(RS-232C), Parallel(IEEE 1284), Ethernet, USB 2.0 HS

EMULATION : BXL / POS

DRIVER : Windows, OPOS, Linux, Virtual COM, Mac

SENSOR : Paper End, Black-mark, Paper Near End, Wall Mounting
Paper Near End(option), Rear Cover Open

POWER SUPPLY : AC 100 ~ 240V / DC 24V, 1.5A

DIMENSIONS (W X L X H mm) : 160 x 239 x 157mm

WEIGHT (STANDARD I/F, NOT PAPER) : A : 2400g / C : 2500g

INTERNATIONAL : FCC, UL, CE, CB, GS, GOST-R, CCC, KCC

OPERATING TEMPERATURE : 0 ~ 40°C (32 ~ 104°F)

STANDARDS : Wall Mount Bracket(RWM - 350), Splash Proof
Cover(RSC - 275), External Buzzer(RBC-100), BIXOLON

OPTION : Melodist(RMB-100),
Ribbon Cartridge(RRC-201BR: Black/Red, RRC-201B: Black)

**Drop-in
3 inch Impact Dot
POS Printer**

SRP-275II

HIGHLIGHTS

- Fastest Print Speed up to 5.1 lps
- Eco-friendly design
- Lowest Standby Power (0.91w)
- Compact Design
- Embedded Power Supply
- Black Mark Sensor
- Fast USB Interface
- USB 2.0 HS
- Large Capacity of Data Buffer
- 64KB Data Buffer
- 256KB NV Image
- Two color printing
- Two different type
- SRP-275IIA(without Auto-cutter)
- SRP-275IIC(with Auto-cutter)