

M11-15 LCD Monitor

Diagonal size	15 inch
Resolution	1024x 768 Pixel, 60 Hz
Contrast Ratio	600:1
Brightness	250 nits
Response Time- total (typical)	8 msec
OSD (On Screen Display)	Controls (bottom): menu, up, down, select, power
	Settings: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall
	Languages: Chinese, English, German, Spanish, Russian, French
	Lockouts: power, user controls
Humidity(noncondensing)	Operating: 20%-80%
	Storage: 10%-90%
Temperature	Operating: 0°C to 40°C (32°F to 104°F)
	Storage: -20°C to 60°C (-4°F to 140°F)
Product Dimension (W/H/D) mm	350mmx50mmx280mm
Color	Black
Viewing Angle	Horizontal & Vertical: ±80° or 160° total
MTBF	50,000 Hours
Horizontal scan rate (KHz)	30 ~ 60 KHz
Vertical scan rate (Hz)	56 ~ 75 Hz
Input video format	Analog VGA
Front Control	Power On/Off with LED, Menu
	AutoTune, Adjustment (+/-)
Built-in Speaker	Optional
Electrical Power	Adapter Input 100-240 VAC, 50-60HZ 1.5A
	Adapter Output 12V DC, 4.2A
Mounting options	75mm x 75mm VESA mount
Weight Gross	2.5Kg
Power Consumption	50W (Max)
Interface	VGA, Audio, Power