



www.vivapos.es

Monitor T-1505 perfecta simplicidad

Te presentamos el nuevo monitor T1505, dirigido a la rápida evolución del punto de venta, al mercado retail, los mercados de hospitality, que proporcionan un funcionamiento fiable, duradero que hará de éste monitor el compañero perfecto de tu pc y software de tpv.

Características

- Económico y fiable
- Formato 4:3
- Hasta 1024 x 768 de resolución a 75 Hz
- Con Tecnología resistiva de cinco hilos
- Interfaz USB
- Soporte de montaje Vesa extraíble
- Sistema de montaje en la parte inferior del pie para la seguridad de mesa
- Sistema de control (OSD) lateral

Model	T1505
LCD Type	15 " A-SiTFT-LCD, 4: 3 screen
Recommend Resolutior	1024×768
Operating Temp.	0~50°C
Touch panel	5 WireResistive
Monitor interface Input	VGA
Power Supply	Type: External brick Input (line) voltage: 100 - 240 VAC, 50-60 Hz Output voltage/current: 12 volts at 4 amps max
Mount Interface	1)VESA 75mm and 100mm 2)Mount bracket, horizontal or vertical
Stand for monitor	Optional
Regular Warranty	1 year for LCD
LCD Brightness	300 cd/m2
Resolution	1024×768@75Hz
Contrast Ratio	700:1
Dot Pitch(mm)	0.099×0.297 (Horizontal x vertical)
Pixel Pich(mm)	0.297×0.297 (Horizontal x vertical)
View area	304.128x228.096 mm (Horizontal x vertical)
Panel dimension	326.5x253.5x9.6 mm
Response time	30(Typ.)(Tr+Td) ms
Viewing angle	80/80/65/80
Best view angle	6 o' clock
Scan frequency	60 Hz
Tube type	WLED
Interface brand	JST
Interface quantity	1pc ,6pins
SingalType	LVDS (1 ch, 8 bit)
Singal interface	HRS,1pc, 20pins
Nominal Input Voltage VDC	+3.3V(Typ)
Support Color	16.7M (6-bit + FRC)
Total power consumption	6.39W
Output	12V/DC/4A
Input	100-240 VAC, 50-60 Hz
MTBF	50000 hr at 25°C

El fabricante se reserva el derecho a cambiar las especificaciones.



Pos Iberica Solutions, S.L.
Travessera de Dalt 69
08024 Barcelona
Tel: 93 285 30 89
comercial@posiberica.com
www.posiberica.com

