





Czar, Commitment to performance excellence

Its hallmark is operation excellence and it objective is to provide the best system for your applications.

With deep roots in the total solutions experience, as well as extensive knowledge and understanding of the market's needs, we have released the 17" Czar all-in-one system hospitality, Kiosk... markets.




Absolutely desirable. Cesar system is here---exquisite all-in-one system with several models available

for your applications. Performance you can feel, a product you can count on.

Main Board	17"Cesar J1900 All-in-one system (Fan-less] PP8100-H27B
	Intel® Celeron® Processor J1900 2.00 GHz
CPU Chipset	Integrated
	2x SO-DIMM (204pin] Slot, DDR3 1333 MHz,Max 8GB
System Memory	Registered DIMM or ECC DIMM is not supported
LCD Panel	
Panel Size	17"
Maximum Resolution	1280 x 3(RGB) x 1024
Brightness	250 cd/m ²
Contrast Ratio	1000:1
Response Time	5 ms
View Angles (H/V)	160 / 150
Touch Panel	Projected Capacitive Multi-Touch Panell (10 point]
Storage	
HDD .	2.5" SATA interface x 2
Expansion	
PCI-E Slot	x 1
Mini PCI-E Slot	x 1(Support mSATA)
Power	
Power Adaptor	Input AC 100-240V 2.5A 50/60Hz, Output DC I2V 6.66A
1/0	
USB	x 5 USB2.0
Serial	x 3 standard RS-232 COM1 with 5V /12V power selectable
LAN	x 1
2nd VGA Output	x 1
PS/2(Keyboard)	x 1
Audio	x 1 Line Out & x 1 Microphone In
Control/indicator	
Power Button LED Indicators	x 1 Power (RED)
	Powel (RED)
Optional Peripherals	100 T
Magnetic Card Reader	ISO Track 1/2/3, USB interface
VFD Customer Display	20 x 2 characters, RS-232 interface
Second Display Second HDD	8"'/10.4" (800 x 600) and 15"(l024x768)
Others	- WIFI, iButton, Printer stand thermal 80mm
Dimensions	WIFI, IDUITOII, FIIITEI STAITU TIEITIIAI OOTIIII
Diffictions	17"PP Czar System 393(W) X 222.5(L) X 371.9(H) mm
Environment	11 11 Ozar System 333(w) x 222.3(c) x 311.3(h) hilli
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	- 20°C ~ 60°C (-6°F ~ 140°F)
Operating Humidity	10% - 80% RH non condensing
Storage Humidity	10% - 80% RH non condensing
Certificate	

IP54 Water proof on the front panel





Travessera de Dalt 69 08024 Barcelona

Tel: 932853089 - Fax: 932953059 Web: www.posiberica.com Mail: comercial@posiberica.com



ΙP